

# Ferrous Ammonium Sulfate, 0.1N (0.1M)

## Safety Data Sheet

Date of issue: 06/27/2013

Revision date: 06/28/2017

Supersedes: 06/28/2017

Version: 1.1

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixtures  
 Product name : Ferrous Ammonium Sulfate, 0.1N (0.1M)  
 Product code : C3902

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.  
 Recommended use : Laboratory chemicals  
 Restrictions on use : Not for food, drug or household use

#### 1.3. Supplier

Lab Alley LLC  
 22111 Highway 71 West, Suite 601  
 Spicewood, Texas 78669  
 Tel.: 512-668-9918

#### 1.4. Emergency telephone number

Emergency number : InfoTrac: 800-535-5053

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin corrosion/irritation H314 Causes severe skin burns and eye damage  
 Category 1B  
 Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger  
 Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage  
 Precautionary statements (GHS-US) : P260 - Do not breathe mist, vapors, spray  
 P264 - Wash exposed skin thoroughly after handling  
 P280 - Wear protective gloves, eye protection  
 P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting  
 P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P310 - Immediately call a poison center or doctor/physician  
 P363 - Wash contaminated clothing before reuse  
 P405 - Store locked up  
 P501 - Dispose of contents/container to comply with local, state and federal regulations  
 If inhaled: Remove person to fresh air and keep comfortable for breathing

#### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None.

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# Ferrous Ammonium Sulfate, 0.1N (0.1M)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Water	(CAS-No.) 7732-18-5	94.08	Not classified
Ferrous Ammonium Sulfate Hexahydrate	(CAS-No.) 7783-85-9	3.92	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Sulfuric Acid	(CAS-No.) 7664-93-9	2	Skin Corr. 1A, H314 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : Causes severe skin burns and eye damage.
- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.
- Symptoms/effects after eye contact : Causes serious eye damage.
- Symptoms/effects after ingestion : Nausea. Vomiting. Diarrhoea.
- Chronic symptoms : Affection/discolouration of the teeth. Cracking of the skin. Inflammation/damage of the eye tissue.

#### 4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Not flammable.
- Explosion hazard : Not applicable.
- Reactivity : Thermal decomposition generates : Corrosive vapors.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Gloves.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

# Ferrous Ammonium Sulfate, 0.1N (0.1M)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mist, vapors, spray.

Hygiene measures : Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : incompatible materials. Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Special rules on packaging : Protect from light.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Ferrous Ammonium Sulfate Hexahydrate (7783-85-9)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> Iron salts, soluble, as Fe
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> Iron salts, soluble, as Fe
Sulfuric Acid (7664-93-9)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (Sulfuric acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Thoracic fraction)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
IDLH	US IDLH (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
Water (7732-18-5)		
Not applicable		

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Face shield. Gloves. Protective clothing. Safety glasses.



#### Hand protection:

Wear protective gloves

# Ferrous Ammonium Sulfate, 0.1N (0.1M)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Eye protection:

Chemical goggles or face shield

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Respiratory protection not required in normal conditions

### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: light green.
Color	: Green
Odor	: Odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: None.

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizers. Strong bases.

# Ferrous Ammonium Sulfate, 0.1N (0.1M)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

Gaseous ammonia. Sulfur compounds. Thermal decomposition generates : Corrosive vapors.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact

Acute toxicity : Not classified

Ferrous Ammonium Sulfate Hexahydrate (7783-85-9)	
LD50 oral rat	3250 mg/kg
ATE US (oral)	3250 mg/kg body weight

Sulfuric Acid (7664-93-9)	
LD50 oral rat	2140 mg/kg body weight (Rat; Experimental value)
ATE US (oral)	2140 mg/kg body weight

Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Sulfuric Acid (7664-93-9)	
Additional information	Strong inorganic acid mists containing sulfuric acid are carcinogenic to humans
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Reproductive toxicity : Not classified  
Based on available data, the classification criteria are not met

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Nausea. Vomiting. Diarrhoea.

Chronic symptoms : Affection/discolouration of the teeth. Cracking of the skin. Inflammation/damage of the eye tissue.

## SECTION 12: Ecological information

### 12.1. Toxicity

Sulfuric Acid (7664-93-9)	
LC50 fish 1	42 mg/l (LC50; 96 h)
EC50 Daphnia 1	29 mg/l (EC50; 24 h)

### 12.2. Persistence and degradability

Ferrous Ammonium Sulfate, 0.1N (0.1M)	
Persistence and degradability	Not established.

# Ferrous Ammonium Sulfate, 0.1N (0.1M)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Ferrous Ammonium Sulfate Hexahydrate (7783-85-9)</b>	
Persistence and degradability	Not established.
<b>Sulfuric Acid (7664-93-9)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>Water (7732-18-5)</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>Ferrous Ammonium Sulfate, 0.1N (0.1M)</b>	
Bioaccumulative potential	Not established.
<b>Ferrous Ammonium Sulfate Hexahydrate (7783-85-9)</b>	
Bioaccumulative potential	Not established.
<b>Sulfuric Acid (7664-93-9)</b>	
Log Pow	-2.2 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.
<b>Water (7732-18-5)</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming	: No known effects from this product.
GWPmix comment	: No known effects from this product.
Other information	: Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN3264 Corrosive liquid, acidic, inorganic, n.o.s., 8, II
UN-No.(DOT)	: UN3264
Proper Shipping Name (DOT)	: Corrosive liquid, acidic, inorganic, n.o.s.
Transport hazard class(es) (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Symbols	: G - Identifies PSN requiring a technical name

# Ferrous Ammonium Sulfate, 0.1N (0.1M)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Sulfuric Acid, ACS	CAS-No. 7664-93-9	2%
--------------------	-------------------	----

#### Ferrous Ammonium Sulfate Hexahydrate (7783-85-9)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

#### Sulfuric Acid (7664-93-9)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

#### 15.2. International regulations

##### CANADA

#### Ferrous Ammonium Sulfate Hexahydrate (7783-85-9)

Not listed on the Canadian DSL (Domestic Substances List)
---

##### EU-Regulations

No additional information available

##### National regulations

# Ferrous Ammonium Sulfate, 0.1N (0.1M)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Ferrous Ammonium Sulfate Hexahydrate (7783-85-9)

Not listed on the Canadian IDL (Ingredient Disclosure List)

### Sulfuric Acid (7664-93-9)

Listed on IARC (International Agency for Research on Cancer)  
Listed as carcinogen on NTP (National Toxicology Program)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

Revision date : 06/28/2017

Other information : None.


Full text of H-phrases: see section 16:

H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 0 - Materials that will not burn under typical dire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



### Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B  
B - Safety glasses, Gloves

SDS US LabChem

*Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and Lab Alley LLC assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.*