

## SAFETY DATA SHEET

Creation Date 19-Sep-2012

Revision Date 01-Apr-2019

Revision Number 1

### 1. Identification

**Product Name** Gram Decolorizer (Enhanced)  
**Cat No. :** C4195  
**Synonyms** Gram's Acetone Alcohol. Gram Stain #3  
**Recommended Use** Laboratory chemicals.  
**Uses advised against** No Information available  
**Details of the supplier of the safety data sheet**

**Company**

Lab Alley LLC  
22111 Highway 71 West, Suite 601  
Spicewood, Texas 78669  
Tel.: 512-668-9918

**Emergency Telephone Number**

InfoTrac: 800-535-5053

### 2. Hazard(s) identification

**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Liver, Blood.	

**Label Elements**

**Signal Word**

Danger

**Hazard Statements**

Highly flammable liquid and vapor  
Causes serious eye irritation  
May cause respiratory irritation  
May cause drowsiness or dizziness  
May cause cancer

Causes damage to organs  
Causes damage to organs through prolonged or repeated exposure



### Precautionary Statements

#### Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection  
Do not breathe dust/fume/gas/mist/vapors/spray  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

#### Response

IF exposed: Call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

### 3. Composition / information on ingredients

Component	CAS-No	Weight %
Acetone	67-64-1	40
Ethyl alcohol	64-17-5	57
Methyl alcohol	67-56-1	3

### 4. First-aid measures

<b>General Advice</b>	If symptoms persist, call a physician.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.
<b>Inhalation</b>	Move to fresh air. If breathing is difficult, give oxygen. Obtain medical attention.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.
<b>Most important symptoms/effects</b>	Breathing difficulties. . Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
<b>Notes to Physician</b>	Treat symptomatically

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.
<b>Unsuitable Extinguishing Media</b>	No information available
<b>Flash Point</b>	-17 °C / 1.4 °F
<b>Method -</b>	No information available
<b>Autoignition Temperature</b>	No information available
<b>Explosion Limits</b>	
<b>Upper</b>	No data available
<b>Lower</b>	No data available
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

### Specific Hazards Arising from the Chemical

Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### Hazardous Combustion Products

None known

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### NFPA

**Health**  
3

**Flammability**  
4

**Instability**  
0

**Physical hazards**  
N/A

## 6. Accidental release measures

<b>Personal Precautions</b>	Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges.
<b>Environmental Precautions</b>	Should not be released into the environment. See Section 12 for additional ecological information.
<b>Methods for Containment and Clean Up</b>	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

<b>Handling</b>	Ensure adequate ventilation. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take
-----------------	---

precautionary measures against static discharges.

**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition.

## 8. Exposure controls / personal protection

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	TWA: 250 ppm STEL: 500 ppm	(Vacated) TWA: 750 ppm (Vacated) TWA: 1800 mg/m <sup>3</sup> (Vacated) STEL: 2400 mg/m <sup>3</sup> (Vacated) STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup>	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m <sup>3</sup> TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m <sup>3</sup> (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m <sup>3</sup> Skin TWA: 200 ppm TWA: 260 mg/m <sup>3</sup>	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>

Component	Quebec	Mexico OEL (TWA)	Ontario TWA/STEL
Acetone	TWA: 500 ppm TWA: 1190 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2380 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> STEL: 1260 ppm STEL: 3000 mg/m <sup>3</sup>	TWA: 500 ppm STEL: 750 ppm
Ethyl alcohol	TWA: 1000 ppm TWA: 1880 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	STEL: 1000 ppm
Methyl alcohol	TWA: 200 ppm TWA: 262 mg/m <sup>3</sup> STEL: 250 ppm STEL: 328 mg/m <sup>3</sup> Skin	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 310 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 250 ppm Skin

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

**Personal Protective Equipment****Eye/face Protection**

Tightly fitting safety goggles. Face-shield.

**Skin and body protection**

Long sleeved clothing.

**Respiratory Protection**

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Clear
<b>Odor</b>	Strong
<b>Odor Threshold</b>	No information available
<b>pH</b>	No information available
<b>Melting Point/Range</b>	No data available
<b>Boiling Point/Range</b>	No information available
<b>Flash Point</b>	-17 °C / 1.4 °F
<b>Evaporation Rate</b>	No information available
<b>Flammability (solid,gas)</b>	Not applicable
<b>Flammability or explosive limits</b>	
<b>Upper</b>	No data available
<b>Lower</b>	No data available
<b>Vapor Pressure</b>	No information available
<b>Vapor Density</b>	No information available
<b>Specific Gravity</b>	No information available
<b>Solubility</b>	No information available
<b>Partition coefficient; n-octanol/water</b>	No data available
<b>Autoignition Temperature</b>	No information available
<b>Decomposition Temperature</b>	No information available
<b>Viscosity</b>	No information available
<b>VOC Content(%)</b>	100

## 10. Stability and reactivity

<b>Reactive Hazard</b>	None known, based on information available
<b>Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
<b>Incompatible Materials</b>	Strong oxidizing agents
<b>Hazardous Decomposition Products</b>	None under normal use conditions
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing.

## 11. Toxicological information

### Acute Toxicity

#### Product Information

##### Oral LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

##### Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

##### Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg ( Rat )	> 15800 mg/kg (rabbit) > 7400 mg/kg (rat)	76 mg/l, 4 h, (rat)
Ethyl alcohol	LD50 = 7060 mg/kg ( Rat )	Not listed	20000 ppm/10H ( Rat )
Methyl alcohol	<b>Calc. ATE 60 mg/kg (Human evidence)</b> LD50 = 6200 mg/kg ( Rat )	<b>Calc. ATE 300 mg/kg (Human evidence)</b> LD50 = 15800 mg/kg ( Rabbit )	<b>Calc. ATE 3.0 mg/l (vapours) or 0.5 mg/l (dust/mists) (Human evidence)</b> LC50 = 64000 ppm ( Rat ) 4 h 83.2 mg/L ( Rat ) 4 h

**Toxicologically Synergistic Products** No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Irritation** No information available

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Acetone	67-64-1	Not listed	Not listed	Not listed	Not listed	Not listed
Ethyl alcohol	64-17-5	Group 1	Known	A3	X	Not listed
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed

*IARC: (International Agency for Research on Cancer)*

*IARC: (International Agency for Research on Cancer)*

*Group 1 - Carcinogenic to Humans*

*Group 2A - Probably Carcinogenic to Humans*

*Group 2B - Possibly Carcinogenic to Humans*

*A1 - Known Human Carcinogen*

*A2 - Suspected Human Carcinogen*

*A3 - Animal Carcinogen*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

**Mutagenic Effects** No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

**STOT - single exposure** Respiratory system Central nervous system (CNS) Optic nerve

**STOT - repeated exposure** Liver Blood

**Aspiration hazard** No information available

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** The toxicological properties have not been fully investigated.

## 12. Ecological information

### Ecotoxicity

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	NOEC = 430 mg/l (algae; 96 h)	Oncorhynchus mykiss: LC50 = 5540 mg/l 96h Alburnus alburnus: LC50 = 11000 mg/l 96h Leuciscus idus: LC50 = 11300 mg/L/48h Salmo gairdneri: LC50 = 6100 mg/L/24h	EC50 = 14500 mg/L/15 min	EC50 = 8800 mg/L/48h EC50 = 12700 mg/L/48h EC50 = 12600 mg/L/48h
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h

		mg/L/5 min	
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min
		EC50 > 10000 mg/L 24h	

**Persistence and Degradability** No information available  
**Bioaccumulation/ Accumulation** No information available.

**Mobility**

Component	log Pow
Acetone	-0.24
Ethyl alcohol	-0.32
Methyl alcohol	-0.74

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-
Methyl alcohol - 67-56-1	U154	-

### 14. Transport information

**DOT**

**UN-No** 1993  
**Proper Shipping Name** FLAMMABLE LIQUIDS, N.O.S.  
**Proper technical name** (Ethanol, Acetone)  
**Hazard Class** 3  
**Packing Group** II

**TDG**

**UN-No** 1993  
**Proper Shipping Name** FLAMMABLE LIQUIDS, N.O.S.  
**Proper technical name** (Ethanol, Acetone)  
**Hazard Class** 3  
**Packing Group** II

**IATA**

**UN-No** 1993  
**Proper Shipping Name** FLAMMABLE LIQUIDS, N.O.S.  
**Hazard Class** 3  
**Packing Group** II

**IMDG/IMO**

**UN-No** 1993  
**Proper Shipping Name** FLAMMABLE LIQUIDS, N.O.S.  
**Hazard Class** 3  
**Packing Group** II

### 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

**International Inventories**

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Acetone	X	X	-	200-662-2	-		X	X	X	X	X
Ethyl alcohol	X	X	-	200-578-6	-		X	X	X	X	X
Methyl alcohol	X	X	-	200-659-6	-		X	X	X	X	X

**Legend:**

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### U.S. Federal Regulations

TSCA 12(b) Not applicable

### SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	3	1.0

### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CWA (Clean Water Act) Not applicable

### Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA Occupational Safety and Health Administration  
Not applicable

### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Acetone	5000 lb	-
Methyl alcohol	5000 lb	-

California Proposition 65 This product contains the following proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic beverages only)	-	Developmental Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

### U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X	-	X
Ethyl alcohol	X	X	X	X	X
Methyl alcohol	X	X	X	X	X

### U.S. Department of Transportation

Reportable Quantity (RQ): Y



DOT Marine Pollutant N  
 DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security**

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard
Acetone	2000 lb STQ

**Other International Regulations**

Mexico - Grade Moderate risk, Grade 2

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B2 Flammable liquid  
 D2A Very toxic materials



## 16. Other information

Prepared By Regulatory Affairs  
 Lab Alley LLC  
 Email: customerservice@laballey.com

Creation Date 19-Sep-2012  
 Revision Date 01-Apr-2019  
 Print Date 11-Dec-19  
 Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

**Disclaimer**

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**